

# UniFi Dream Machine Professional USM-Pro

## Datasheet

### Mechanical


Dimensions	442.4 x 43.7 x 285.6 mm (17.4 x 1.7 x 11.2")
Weight	3.9 kg (8.6 lb)
Enclosure material	Aluminium CNC, SGCC steel
Mount material	SGCC steel

### Hardware

Processor	Quad-core ARM® Cortex®-A57 at 1.7 GHz
System memory	4 GB DDR4
On-board storage	16 GB eMMC
Management interface	Ethernet Bluetooth
Networking interface	(8) LAN: GbE RJ45 ports (1) WAN: GbE RJ45 port
IDS/IPS throughput	3.5 Gbps* *Measured with iPerf3.
Power method	(1) Universal AC Input, 100—240V AC, 50/60 Hz (1) USP-RPS DC input
Power supply	AC/DC, internal, 50W
Supported voltage range	100—240V AC
Max. power consumption	33W
ESD/EMP protection	Air: ± 15kV, contact: ± 8kV
LCM display	(1) 1.3" touchscreen
Button	Factory reset
Operating temperature	-10° to 40° C (14° to 104° F)
Operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

### LEDs

Ethernet	Link/activity Green: 1G Amber: 10/100M
SFP+	Link/activity White: 10G Green: 1G
HDD	White: disk activity Amber: disk error
RPS	Blue: ready



\*Requires UniFi Power Backup.

Email: [next@minitel.pt](mailto:next@minitel.pt)

Telemóvel: 213810900

[www.minitelfnext.com](http://www.minitelfnext.com)

UBIQUITI  
NETWORKS

minitel  
NEXT